Internal Doc ID #: Date:

ISTA 6 - Amazon.com - SIOC - F Test Report_External

VERSION DATE: 4/5/2018

ITEM INFORMATION						
Vendor/Seller Nam	Vendor/Seller Name:					
ASIN:						
Item:						
Certification Passe	☐ Pass: Tier 2-	Frustration Free Packaging (FFP) Ships In Own Container (SIOC) nforced Over Box (EOB)				
LAB INFORMATION	N					
Testing Lab:						
Location:						
Date of Test:						
ISTA Member/ Lab	Tech:					
TEST RESULTS						
		Tested Item Summary				
Number of Sar	mples Tested	Number of Samples Passed	Number of Samples Failed			
Post Test Commen	ts:					
Overview						
Product Condition						
Packaging Condition						

Standard Company Disclaimer:

Internal Doc ID #: Date:

AB TEST REQUEST (filled	out by requestor}		
Test Requestor			
Project Name			
Submission Date			
Due Date			
ASIN	Manufacturer	Description	
	•		
Package Dimension			
Package Weight			
Classification 1			
Classification 2		LTL	
Test Type		ISTA 6 –Amazon.com SIOC – F	
Fragile/Non-Fragile			
Value Add Packaging			
(VAP)			
Value Add Packaging			
(VAP) Info			
Total Test Samples			
Additional Notes			
RE-TEST INSPECTION (fil	lled out by lab}		
Product Condition			
Package Condition			
Package Condition		ORIGINAL as arrived in the lab for testing	
before testing		W re-packaged with new materials before testing	
		w re-packaged with new materials before testing	
Corrugated Info (Box Cert if available)			
Dunnage Info			
Additional Notes			

Internal Doc ID #: Date:

PRE-TEST PICTURES

Six sides of the ASIN package should be numbered and photographed. If a box cert is present it should be taken and recorded. Isometric picture views should be taken as called out below. Pictures of special call outs and or damage should have description of location and detailed information in the text box below the picture.

Side 1	Side 2	Side 3			
Cido 4	C:do F	C:40 C			
Side 4 Side 5 Side 6					
Box Cert (If Applicable)	ISO #1 Side 1/2/5	ISO #2 Sides 3/4/6			

TEST DETAIL

Items in black were completed and values updated. Items left in gray were not completed.

Test	Value	P/F	P/F	P/F	P/F	P/F	OBSERVATIONS
BLOCK 1:Temp and Humidity							Ambient Lab Temp 12+ hours
BLOCK 3: Tip/Tip Over	Pass/fail						
BLOCK 5: Rotational FLAT Drop	Pass/fail						
BLOCK 6: Rotational EDGE Drop	Pass/fail						
BLOCK 7: Rotational CORNER Drop	Pass/fail						
BLOCK 8: Inclined or Horizontal Impact							
BLOCK 9: Compression Horizontal							
BLOCK 11: Fork Lift Simulation	Pass/fail						
BLOCK 14: Pallet Vib with Top Load							
BLOCK 17: Pallet Rotational FLAT Drop	Pass/fail						
BLOCK 18: Pallet Rotational EDGE Drop	Pass/fail						
BLOCK 19: Pallet Rotational CORNER Drop	Pass/fail						
BLOCK 20: Inclined or Horizontal Impact							
BLOCK 24: Concentrated Edge Impact	Pass/fail						

TEST PICTURES

Pictures should be taken of each block test set up along with a post picture taken of the item at the end of each test block.

Additional pictures of damage should have locations noted, size of damages measured, and written in text box below them.

Diagle 2 Test Cat III	Diock 2 Doct Tost Itom Distunc	
Block 3 Test Set Up	Block 3 Post Test Item Picture	

Block 5 Test Set Up	Block 5 Post Test Item Picture	
Block 6 Test Set Up	Block 6 Post Test Item Picture	
Block 7 Test Set Up	Block 7 Post Test Item Picture	

Block 8 Test Set Up	Block 8 Post Test Item Picture	
Block 9 Test Set Up	Block 9 Post Test Item Picture	
Block 11 Test Set Up	Block 11 Post Test Item Picture	

Block 14 Face 3 Test Set up	Block 14 Face 3 Post Test Item Picture	Block 14 Face 3 Test Vibration Profile
Block 17 Test Set Up	Block 17 Post Test Item Picture	
Block 18 Test Set Up	Block 18 Post Test Item Picture	
piocy to lest set oh	PIOCK TO LOST 1621 HEILI LICTUIE	

Block 19 Test Set Up	Block 19 Post Test Item Picture	
·		
Block 20 Test Set Up	Block 20 Post Test Item Picture	
Block 24 Test Set Up	Block 24 Post Test Item Picture	

				RFS

Isometric views of the box should be taken as called out in first two picture spots. An exploded bill of material (BOM) view should be added to the third slot. Additional pictures of damage should have locations noted, size of damages measured, and written in text box below them.

ISO #1 Side 1/2/5	ISO #2 Sides 3/4/6	Exploded BOM View

END OF REPORT